

s.n. 10/644,748

Page 2

IN THE CLAIMS

Cancel claim 27, amend claims 1, 2, 13, 19, 25, 28, 35, 40, 44, 49, 50, 52, 53, 60 and 63, and add new claim 65 such that the new claim set reads as follows:

1. (Currently Amended) A method of drilling a directional or horizontal wellbore in a hydrocarbon formation, comprising:

providing a concentric drill string consisting essentially of an inner pipe having an inside wall and an outside wall and an outer pipe having an inside wall and an outside wall, said outside wall of said inner pipe and said inside wall of said outer pipe defining an annulus between the pipes;

connecting a bottomhole assembly, said bottomhole assembly comprising a directional drilling means for forming a borehole, to the concentric drill string; and

delivering drilling medium through one of said annulus or inner pipe to the directional drilling means and removing exhaust drilling medium by extracting said exhaust drilling medium primarily through said other of said annulus or inner pipe and to the surface of the wellbore by means of said other of said annulus or inner pipe.

2. (Previously Presented) A method of drilling a directional or horizontal wellbore in a hydrocarbon formation, comprising:

providing a concentric drill string consisting essentially of an inner pipe having an inside wall and an outside wall and an outer pipe having an inside wall and an outside wall, said outside wall of said inner pipe and said inside wall of said outer pipe defining an annulus between the pipes;

connecting a bottomhole assembly, said bottomhole assembly comprising a directional drilling means for forming a borehole and one or more tools selected from the group consisting of a downhole data collection and transmission means, a shock sub, a drill collar and an interchange means, to the concentric drill string; and

s.n. 10/644,748

Page 3

delivering drilling medium through one of said annulus or inner pipe to the directional drilling means and removing exhaust drilling medium by extracting said exhaust drilling medium through said other of said annulus or inner pipe and to the surface of the wellbore by means of said other of said annulus or inner pipe.

3. (Previously Presented) The method of claim 1 or 2 wherein the drilling medium is delivered through the annulus and the exhaust drilling medium is extracted through the inner pipe.
4. (Previously Presented) The method of claim 1 or 2 wherein the drilling medium is delivered through the inner pipe and exhaust drilling medium is extracted through the annulus.
5. (Previously Presented) The method of claim 1 or 2 wherein drilling cuttings are extracted together with the exhaust drilling medium.
6. (Previously Presented) The method of claim 1 or 2 wherein drilling cuttings and hydrocarbons are extracted together with the exhaust drilling medium.
7. (Previously Presented) The method of claim 1 or 2 wherein said directional drilling means is a reverse circulating directional drilling means.
8. (Previously Presented) The method of claim 1 or 2, said bottomhole assembly further comprising a downhole flow control means positioned at or near the directional drilling means, said method further comprising preventing a flow of hydrocarbons from the inner pipe or the annulus or both to the surface of the wellbore by operation of said downhole flow control means.
9. (Previously Presented) The method of claim 1 or 2 further comprising providing a surface flow control means positioned at or near the surface of the wellbore for preventing flow of hydrocarbons from a space between the outside wall of the outer pipe and a wall of the wellbore.
10. (Previously Presented) The method of claim 9, said surface flow control means further comprising a discharging means, said method further comprising removing said exhaust drilling medium through said discharging means from said wellbore.

s.n. 10/644,748

Page 4

11. (Previously Presented) The method of claim 10 wherein said discharging means further comprises a flare means for flaring hydrocarbons produced from the wellbore.

12. (Previously Presented) The method of claim 1 or 2 wherein said drilling medium comprises air and said directional drilling means comprises a reciprocating air hammer, a drill bit and a bent sub or housing.

13. (Currently Amended) The method of claim 1 or 2 wherein said drilling medium comprises air and said directional drilling means comprises a rotary drill bit, ~~a rotary table or top drive drilling system~~ and a bent sub or housing, said directional drilling means being operated by a rotary table or top drive drilling system.

14. (Previously Presented) The method of claim 1 or 2 wherein said drilling medium comprises air and said directional drilling means comprises a drill bit, a steerable downhole air motor and a bent sub or housing.

15. (Previously Presented) The method of claim 14 wherein said steerable downhole air motor is a reverse circulating steerable downhole air motor.

16. (Previously Presented) The method of claim 1 or 2 wherein said drilling medium comprises drilling mud and said directional drilling means comprises a drill bit, a mud motor and a bent sub or housing.

17. (Previously Presented) The method of claim 16 wherein said mud motor is a reverse circulating mud motor.

18. (Previously Presented) The method of claim 12 wherein said reciprocating air hammer is a reverse circulating reciprocating air hammer.

19. (Currently Amended) The method of claim 1 or 2 wherein said drilling medium is selected from the group consisting of drilling mud, drilling fluid, gases and a combination thereof, ~~mixture of drilling fluid and gas~~ and said directional drilling means comprises a drill bit, ~~a rotary table or top drive drilling system~~ and a bent sub or housing.

s.n. 10/644,748

Page 5

20. (Previously Presented) The method of claim 1 or 2, said directional drilling means further comprising a venturi, said method further comprising accelerating said exhaust drilling medium through said venturi so as to facilitate removal of said exhaust drilling medium from the concentric drill string.

21. (Previously Presented) The method of claim 1 or 2 further comprising providing a shroud means positioned between the outside wall of the outer pipe and a wall of the wellbore for preventing release of exhaust drilling medium outside the concentric drill string and into the formation.

22. (Previously Presented) The method of claim 1 or 2 further comprising providing a suction type compressor means for extracting said exhaust drilling medium through said annulus or inner pipe.

23. (Previously Presented) The method of claim 2 wherein said downhole data collection and transmission means comprises a measurement-while-drilling tool or a logging-while drilling tool or both.

24. (Previously Presented) The method of claim 1 further comprising providing an interchange means for directing said exhaust drilling medium through said annulus or inner pipe.

25. (Currently Amended) An apparatus for drilling a directional or horizontal wellbore in a hydrocarbon formation, comprising:

a concentric drill string consisting essentially of an inner pipe having an inside wall and an outside wall and an outer pipe having an inside wall and an outside wall, said outside wall of said inner pipe and said inside wall of said outer pipe defining an annulus between the pipes;

a bottomhole assembly, said bottomhole assembly comprising a directional drilling means for forming a borehole and one or more tools selected from the group consisting of a downhole data collection and transmission means, a shock sub, a drill collar and an interchange means for directing said drilling medium and entrained drill cuttings through said annulus or inner pipe, operably connected to the concentric drill string; and

s.n. 10/644,748

Page 6

a drilling medium delivery means for delivering drilling medium through one of said annulus or inner pipe to the directional drilling means for entraining and removing drill cuttings through said other of said annulus or inner pipe.

26. (Previously Presented) The apparatus of claim 25 wherein said bottomhole assembly further comprising a downhole flow control means positioned at or near the directional drilling means for preventing flow of hydrocarbons from the inner pipe or the annulus or both to the surface.

27. (Canceled) The apparatus of claim 25 wherein said bottomhole assembly further comprises one or more tools selected from the group consisting of a downhole data collection and transmission means, a shock sub, a drill collar, a interchange means for directing said drilling medium and entrained drill cuttings through said annulus or inner pipe, and a downhole flow control means.

28. (Currently Amended) The apparatus of claim 27 wherein said downhole data collection and transmission means comprises a measurement-while-drilling tool or a logging-while drilling tool or both.

29. (Previously Presented) The apparatus of claim 25 further comprising a surface flow control means positioned at or near the surface of the wellbore for preventing flow of hydrocarbons from a space between the outside wall of the outer pipe and a wall of the wellbore.

30. (Previously Presented) The apparatus of claim 29 further comprising a discharging means attached to said surface flow control means for discharging said drilling medium and said entrained drill cuttings from the wellbore.

31. (Previously Presented) The apparatus of claim 30 further comprising a flare means attached to said discharging means for flaring hydrocarbons produced from the wellbore.

32. (Previously Presented) The apparatus of claim 25 wherein said directional drilling means is a reverse circulating directional drilling means.

s.n. 10/644,748

Page 7

33. (Previously Presented) The apparatus of claim 25 wherein drilling medium comprises air and directional drilling means comprises a reciprocating air hammer, a drill bit and a bent sub or housing.

34. (Previously Presented) The apparatus of claim 33 wherein said reciprocating air hammer is a reverse circulating reciprocating air hammer.

35. (Currently Amended) The apparatus of claim 25 wherein drilling medium comprises air and directional drilling means comprises a rotary drill bit, ~~a rotary table or top drive system~~ and a bent sub or housing, said directional drilling means being operated by a rotary table or top drive drilling system.

36. (Previously Presented) The apparatus of claim 25 wherein said drilling medium comprises air and said directional drilling means comprises a drill bit, a steerable downhole air motor and a bent sub or housing.

37. (Previously Presented) The apparatus of claim 36 wherein said steerable downhole air motor is a reverse circulating steerable downhole air motor.

38. (Previously Presented) The apparatus of claim 25 wherein said drilling medium comprises drilling mud and said directional drilling means comprises a drill bit, a downhole mud motor and a bent sub or housing.

39. (Previously Presented) The apparatus of claim 38 wherein said downhole mud motor is a reverse circulating downhole mud motor.

40. (Currently Amended) The apparatus of claim 25 wherein drilling medium is selected from the group consisting of drilling mud, drilling fluid and gases and a combination thereof, ~~mixture of drilling fluid and gas~~, and said directional drilling means comprises a drill bit, ~~a rotary table or top drive system~~ and a bent sub or housing.

41. (Previously Presented) The apparatus of claim 25, wherein the directional drilling means further comprising a venturi for accelerating said drilling medium so as to facilitate removal of said drill cuttings from the concentric drill string.

s.n. 10/644,748

Page 8

42. (Previously Presented) The apparatus of claim 25 further comprising a shroud means positioned between the outside wall of the outer pipe and a wall of the wellbore for preventing release of drilling medium or entrained drill cuttings or both outside the concentric drill string and into the formation.

43. (Previously Presented) The apparatus of claim 25 further comprising a suction type compressor means positioned at or near the top of the wellbore for extracting said entrained drill cuttings through said annulus or inner pipe.

44. (Currently Amended) A method of drilling a directional or horizontal wellbore in a hydrocarbon formation, comprising:

providing a concentric drill string comprising an inner pipe, said inner pipe having an inside wall and an outside wall, and an outer pipe having an inside wall and an outside wall, said outside wall of said inner pipe and said inside wall of said outer pipe defining an annulus between the pipes;

connecting a bottomhole assembly, said bottomhole assembly comprising a directional drilling means for forming a borehole, to the concentric drill string; and

delivering drilling medium through said inner pipe to said directional drilling means and removing exhaust drilling medium by extracting said exhaust drilling medium primarily through said annulus and to the surface of the wellbore by means of said annulus.

45. (Previously Presented) A method of drilling a directional or horizontal wellbore in a hydrocarbon formation, comprising the steps of:

providing a concentric drill string comprising an inner pipe, said inner pipe having an inside wall and an outside wall, and an outer pipe having an inside wall and an outside wall, said outside wall of said inner pipe and said inside wall of said outer pipe defining an annulus between the pipes;

connecting a bottomhole assembly, said bottomhole assembly comprising a directional drilling means for forming a borehole, to the concentric drill string;

s.n. 10/644,748

Page 9

delivering drilling medium through one of said annulus or inner pipe to said directional drilling means and removing exhaust drilling medium by extracting said exhaust drilling medium through said other of said annulus or inner pipe; and

providing a downhole flow control means positioned at or near the directional drilling means, for preventing a flow of hydrocarbons from the inner pipe or the annulus or both to the surface of the wellbore by operation of said downhole flow control means.

46. (Previously Presented) A method of drilling a directional or horizontal wellbore in a hydrocarbon formation, comprising the steps of:

providing a concentric drill string comprising an inner pipe, said inner pipe having an inside wall and an outside wall, and an outer pipe having an inside wall and an outside wall, said outside wall of said inner pipe and said inside wall of said outer pipe defining an annulus between the pipes;

connecting a bottomhole assembly, said bottomhole assembly comprising a directional drilling means for forming a borehole, to the concentric drill string;

delivering drilling medium through one of said annulus or inner pipe to said directional drilling means and removing exhaust drilling medium by extracting said exhaust drilling medium through said other of said annulus or inner pipe; and

providing a surface flow control means positioned at or near the surface of the wellbore for preventing flow of hydrocarbons from a space between the outside wall of the outer pipe and a wall of the wellbore.

47. (Previously Presented) The method of claim 46, said surface flow control means further comprising a discharging means, said method further comprising the step of removing said exhaust drilling medium through said discharging means from said wellbore.

48. (Previously Presented) The method of claim 47 wherein said discharging means further comprises a flare means for flaring hydrocarbons produced from the wellbore.

s.n. 10/644,748

Page 10

49. (Currently Amended) A method of drilling a directional or horizontal wellbore in a hydrocarbon formation, comprising:

providing a concentric drill string comprising an inner pipe, said inner pipe having an inside wall and an outside wall, and an outer pipe having an inside wall and an outside wall, said outside wall of said inner pipe and said inside wall of said outer pipe defining an annulus between the pipes;

connecting a bottomhole assembly comprising a directional drilling means, said directional drilling means comprising a rotary drill bit, ~~a rotary table or top drive drilling system~~ and a bent sub or housing for forming a borehole and said directional drilling means being operated by a rotary table or top drive drilling system, to the concentric drill string; and

delivering drilling medium comprising air through one of said annulus or inner pipe to said directional drilling means and removing exhaust drilling medium by extracting said exhaust drilling medium through said other of said annulus or inner pipe.

50. (Currently Amended) A method of drilling a directional or horizontal wellbore in a hydrocarbon formation, comprising:

providing a concentric drill string comprising an inner pipe, said inner pipe having an inside wall and an outside wall, and an outer pipe having an inside wall and an outside wall, said outside wall of said inner pipe and said inside wall of said outer pipe defining an annulus between the pipes;

connecting a bottomhole assembly comprising a directional drilling means, said directional drilling means comprising a drill bit, a reverse circulating steerable downhole air motor and a bent sub or housing for forming a borehole, to the concentric drill string; and

delivering drilling medium comprising air through one of said annulus or inner pipe to said directional drilling means and removing exhaust drilling medium by extracting said exhaust drilling medium through said other of said annulus or inner pipe and to the surface of the wellbore by means of said other of said annulus or inner pipe.

s.n. 10/644,748

Page 11

51. (Previously Presented) A method of drilling a directional or horizontal wellbore in a hydrocarbon formation, comprising:

providing a concentric drill string comprising an inner pipe, said inner pipe having an inside wall and an outside wall, and an outer pipe having an inside wall and an outside wall, said outside wall of said inner pipe and said inside wall of said outer pipe defining an annulus between the pipes;

connecting a bottomhole assembly comprising a directional drilling means, said directional drilling means comprising a drill bit, a reverse circulating mud motor and a bent sub or housing for forming a borehole, to the concentric drill string; and

delivering drilling medium comprising drilling mud through one of said annulus or inner pipe to said directional drilling means and removing exhaust drilling medium by extracting said exhaust drilling medium through said other of said annulus or inner pipe.

52. (Currently Amended) A method of drilling a directional or horizontal wellbore in a hydrocarbon formation, comprising:

providing a concentric drill string comprising an inner pipe, said inner pipe having an inside wall and an outside wall, and an outer pipe having an inside wall and an outside wall, said outside wall of said inner pipe and said inside wall of said outer pipe defining an annulus between the pipes;

connecting a bottomhole assembly comprising a directional drilling means, said directional drilling means comprising a reverse circulating reciprocating air hammer, a drill bit and a bent sub or housing for forming a borehole, to the concentric drill string; and

delivering drilling medium comprising air through one of said annulus or inner pipe to said directional drilling means and removing exhaust drilling medium by extracting said exhaust drilling medium through said other of said annulus or inner pipe and to the surface of the wellbore by means of said other of said annulus or inner pipe.

53. (Currently Amended) A method of drilling a directional or horizontal wellbore in a hydrocarbon formation, comprising:

s.n. 10/644,748

Page 12

providing a concentric drill string comprising an inner pipe, said inner pipe having an inside wall and an outside wall, and an outer pipe having an inside wall and an outside wall, said outside wall of said inner pipe and said inside wall of said outer pipe defining an annulus between the pipes;

connecting a bottomhole assembly comprising a directional drilling means, said directional drilling means comprising a drill bit, ~~a rotary table or top drive drilling system~~ and a bent sub or housing for forming a borehole and said directional drilling means being operated by a rotary table or top drive drilling system, to the concentric drill string; and

delivering drilling medium selected from the group consisting of drilling mud, drilling fluid, gases and a ~~mixture of drilling fluid and gas~~ combination thereof, through one of said annulus or inner pipe to said directional drilling means and removing exhaust drilling medium by extracting said exhaust drilling medium through said other of said annulus or inner pipe.

54. (Previously Presented) A method of drilling a directional or horizontal wellbore in a hydrocarbon formation, comprising the steps of:

providing a concentric drill string comprising an inner pipe, said inner pipe having an inside wall and an outside wall, and an outer pipe having an inside wall and an outside wall, said outside wall of said inner pipe and said inside wall of said outer pipe defining an annulus between the pipes;

connecting a bottomhole assembly, said bottomhole assembly comprising a directional drilling means for forming a borehole, to the concentric drill string;

delivering drilling medium through one of said annulus or inner pipe to said directional drilling means and removing exhaust drilling medium by extracting said exhaust drilling medium through said other of said annulus or inner pipe; and

providing a shroud means positioned between the outside wall of the outer pipe and a wall of the wellbore for preventing release of exhaust drilling medium outside the concentric drill string and into the formation.

s.n. 10/644,748

Page 13

55. (Previously Presented) An apparatus for drilling a directional or horizontal wellbore in a hydrocarbon formation, comprising:

a concentric drill string comprising an inner pipe, said inner pipe having an inside wall and an outside wall, and an outer pipe having an inside wall and an outside wall, said outside wall of said inner pipe and said inside wall of said outer pipe defining an annulus between the pipes;

a bottomhole assembly, said bottomhole assembly comprising a directional drilling means for forming a borehole and a downhole flow control means positioned at or near the directional drilling means for preventing flow of hydrocarbons from the inner pipe or the annulus or both to the surface of the wellbore, operably connected to the concentric drill string; and

a drilling medium delivery means for delivering drilling medium through one of said annulus or inner pipe to the directional drilling means for entraining and removing drill cuttings through said other of said annulus or inner pipe.

56. (Previously Presented) An apparatus for drilling a directional or horizontal wellbore in a hydrocarbon formation, comprising:

a concentric drill string comprising an inner pipe, said inner pipe having an inside wall and an outside wall, and an outer pipe having an inside wall and an outside wall, said outside wall of said inner pipe and said inside wall of said outer pipe defining an annulus between the pipes;

a bottomhole assembly, said bottomhole assembly comprising a directional drilling means for forming a borehole, operably connected to the concentric drill string;

a drilling medium delivery means for delivering drilling medium through one of said annulus or inner pipe to the directional drilling means for entraining and removing drill cuttings through said other of said annulus or inner pipe; and

s.n. 10/644,748

Page 14

a surface flow control means positioned at or near the surface of the wellbore for preventing flow of hydrocarbons from a space between the outside wall of the outer pipe and a wall of the wellbore.

57. (Previously Presented) The apparatus of claim 56 further comprising a discharging means attached to said surface flow control means for discharging said drilling medium and said entrained drill cuttings from the wellbore.

58. (Previously Presented) The apparatus of claim 57 further comprising a flare means attached to said discharging means for flaring hydrocarbons produced from the wellbore.

59. (Previously Presented) An apparatus for drilling a directional or horizontal wellbore in a hydrocarbon formation, comprising:

a concentric drill string comprising an inner pipe, said inner pipe having an inside wall and an outside wall, and an outer pipe having an inside wall and an outside wall, said outside wall of said inner pipe and said inside wall of said outer pipe defining an annulus between the pipes;

a bottomhole assembly comprising a directional drilling means, said directional drilling means comprising a reverse circulating reciprocating air hammer, a drill bit and a bent sub or housing for forming a borehole, operably connected to the concentric drill string; and

a drilling medium delivery means for delivering drilling medium comprising air through one of said annulus or inner pipe to the directional drilling means for entraining and removing drill cuttings through said other of said annulus or inner pipe.

60. (Currently Amended) An apparatus for drilling a directional or horizontal wellbore in a hydrocarbon formation, comprising:

a concentric drill string comprising an inner pipe, said inner pipe having an inside wall and an outside wall, and an outer pipe having an inside wall and an outside wall, said outside wall of said inner pipe and said inside wall of said outer pipe defining an annulus between the pipes;

s.n. 10/644,748

Page 15

a bottomhole assembly comprising a directional drilling means, said directional drilling means comprising a rotary drill bit, ~~a rotary table or top drive system~~ and a bent sub or housing for forming a borehole and said directional drilling means being operated by a rotary table or top drive drilling system, operably connected to the concentric drill string; and

a drilling medium delivery means for delivering drilling medium comprising air through one of said annulus or inner pipe to the directional drilling means for entraining and removing drill cuttings through said other of said annulus or inner pipe.

61. (Previously Presented) An apparatus for drilling a directional or horizontal wellbore in a hydrocarbon formation, comprising:

a concentric drill string comprising an inner pipe, said inner pipe having an inside wall and an outside wall, and an outer pipe having an inside wall and an outside wall, said outside wall of said inner pipe and said inside wall of said outer pipe defining an annulus between the pipes;

a bottomhole assembly comprising a directional drilling means, said directional drilling means comprising a drill bit, a reverse circulating steerable downhole air motor and a bent sub or housing for forming a borehole, operably connected to the concentric drill string; and

a drilling medium delivery means for delivering drilling medium comprising air through one of said annulus or inner pipe to the directional drilling means for entraining and removing drill cuttings through said other of said annulus or inner pipe.

62. (Previously Presented) An apparatus for drilling a directional or horizontal wellbore in a hydrocarbon formation, comprising:

a concentric drill string comprising an inner pipe, said inner pipe having an inside wall and an outside wall, and an outer pipe having an inside wall and an outside wall, said outside wall of said inner pipe and said inside wall of said outer pipe defining an annulus between the pipes;

s.n. 10/644,748

Page 16

- a bottomhole assembly comprising a directional drilling means, said directional drilling means comprising a drill bit, a reverse circulating downhole mud motor and a bent sub or housing for forming a borehole, operably connected to the concentric drill string; and
- a drilling medium delivery means for delivering drilling medium comprising drilling mud through one of said annulus or inner pipe to the directional drilling means for entraining and removing drill cuttings through said other of said annulus or inner pipe.

63. (Currently Amended) An apparatus for drilling a directional or horizontal wellbore in a hydrocarbon formation, comprising:

- a concentric drill string comprising an inner pipe, said inner pipe having an inside wall and an outside wall, and an outer pipe having an inside wall and an outside wall, said outside wall of said inner pipe and said inside wall of said outer pipe defining an annulus between the pipes;
- a bottomhole assembly comprising a directional drilling means, said directional drilling means comprising a drill bit, ~~a rotary table or top drive system~~ and a bent sub or housing for forming a borehole and said directional drilling means being operated by a rotary table or top drive drilling system, operably connected to the concentric drill string; and
- a drilling medium delivery means for delivering drilling medium selected from the group consisting of drilling mud, drilling fluid, gases and a ~~mixture of drilling fluid and gas~~ combination thereof through one of said annulus or inner pipe to the directional drilling means for entraining and removing drill cuttings through said other of said annulus or inner pipe.

64. (Previously Presented) An apparatus for drilling a directional or horizontal wellbore in a hydrocarbon formation, comprising:

- a concentric drill string comprising an inner pipe, said inner pipe having an inside wall and an outside wall, and an outer pipe having an inside wall and an outside wall, said outside wall of said inner pipe and said inside wall of said outer pipe defining an annulus between the pipes;

s.n. 10/644,748

Page 17

a bottomhole assembly, said bottomhole assembly comprising a directional drilling means for forming a borehole, operably connected to the concentric drill string;

a drilling medium delivery means for delivering drilling medium through one of said annulus or inner pipe to the directional drilling means for entraining and removing drill cuttings through said other of said annulus or inner pipe; and

a shroud means positioned between the outside wall of the outer pipe and a wall of the wellbore for preventing release of drilling medium or entrained drill cuttings or both outside the concentric drill string and into the formation.

65. (New) A method of drilling a directional or horizontal wellbore in a hydrocarbon formation, comprising:

providing a concentric drill string consisting essentially of an inner pipe having an inside wall and an outside wall and an outer pipe having an inside wall and an outside wall, said outside wall of said inner pipe and said inside wall of said outer pipe defining an annulus between the pipes;

connecting a bottomhole assembly, said bottomhole assembly comprising a directional drilling means for forming a borehole, to the concentric drill string; and

delivering drilling medium through said annulus to the directional drilling means and removing exhaust drilling medium by extracting said exhaust drilling medium through said inner pipe.